

**COSMOS BRAKE FLUID DOT 3**

COSMOS Brake Fluid DOT 3 are heavy-duty synthetic brake fluid. These fluids are suitable for all conventional drum and disc brake systems that require this performance levels in operation under severe conditions. These brake fluids are recommended for all hydraulic braking system, like disc drum, ABS and clutches, etc., and are suitable for all rubber like SBR, EPDM, Natural & Silicon, etc.

FEATURES & BENEFITS

- Low vapour pressure
- Compatible with seals
- High boiling point especially formulated for disc brakes
- Recommended for use in passenger cars, commercial road transport, off-highway vehicles, agricultural tractors and motorcycles.

PERFORMANCE LEVEL

SAE J1703

FMVSS No. 116 DOT3

ISO 4925

TYPICAL CHARACTERISTICS

Properties	Typical Value
FMVSS Grade	DOT 3
Density @ 20°C	1.032
Viscosity @ 40 C	Report
Viscosity @ 100 C	1.9
Equilibrium Reflux Boiling Pt, °C	>205
Wet Equilibrium Reflux Boiling Pt, °C	150
Water Content, wt%	<0.2
pH (50% vol. aqueous ethanol solution)	8.7

These characteristics are typical of current production. Whilst future production will conform to COSMOS's specification, variations in these characteristics may occur.

HANDLING, HEALTH AND SAFETY

- Lubricants under normal conditions of use, presents no particular toxic hazard. All lubricants, of any kind should be handled with great care, particularly avoiding any contact with skin.
- Prevent any splashing and keep away from combustible materials. Store under cover and away from any risk of pollution. Dispose off used oil correctly; don't pour down drains, into water courses or the soil.
- Take used oil to an authorized collection point.
- COSMOS will not accept any liability if the product is used other than in manner or with the precautions for the purpose specified, and hence advice should be obtained from COSMOS's local office.